

**SOUTHWEST RESEARCH INSTITUTE®**  
**QUARTERLY STATUS AND PROGRESS REPORT**  
**FOR PERIOD ENDING JUNE 8, 2004**

**OTHER TRANSACTION AGREEMENT DTRS56-03-T-0013**  
**SwRI® PROJECT 14.10062**

**“HIGH-POWER LONG-RANGE GUIDED-WAVE INSPECTION OF PIPELINES**

Approximately one-half of the nation’s supply of crude oil and petroleum products and virtually all of its natural gas supplies are transported through a pipeline network over 2 million miles long. Since a majority of these pipelines are operated at high pressure, and some carry hazardous liquids, pipeline failure can cause severe damage to human health, property, and the environment. One of the inspection technologies that has recently emerged for enhanced pipeline safety is the long-range guided-wave technology. This technology can inspect long sections of pipeline (typically more than 100 feet from the sensor in either direction in aboveground pipe for detection of 2- to 3-percent internal and external corrosion defects) and is useful for inspection of buried and unpiggable pipelines. Due to high wave attenuation in buried pipelines, however, the range of inspection presently achievable is relatively short (about 20 feet for detection of 10-percent defects in bitumen-coated pipelines with approximately 0.5-dB/ft attenuation). To be economical for buried pipe inspection, the inspection range needs to be increased.

This project is aimed at producing a high-amplitude guided wave so that a significantly longer length of piping than is presently achievable could be inspected. Based on the magnetostrictive sensor (MsS) guided-wave technology, the high power would be achieved by a combination of technical approaches that include better sensor materials, multiple sensors, and sensor optimization. The target goal of the project is a twenty-fold increase in the guided-wave signal amplitude that would double the current inspection range in buried pipelines. Industrial partners in this project include the Pipeline Research Council International, Southern California Gas Company, Gulf South Pipeline Company, and Southwest Research Institute.

The combined power-enhancing techniques were evaluated in the field. In aboveground pipelines, inspection of more than 250 feet of line containing a 90-degree elbow was achievable in one direction. Also within 50 feet, 0.3- to 0.5-percent defects were detectable. In spite of the enhanced guided-wave power, the detection range of 20- to 30-percent reflectors was found to be no more than 30 feet in buried lines because of a very high wave attenuation (in the range of 1 to 2.5 dB/ft) in the lines tested. Further field evaluations of the high-power guided waves are planned.

*Contact:* Hegeon Kwun, Ph.D.  
Staff Scientist  
Southwest Research Institute  
6220 Culebra Road  
San Antonio, Texas 78238  
(210) 522-3359 phone  
(210) 684-4822 fax  
[hkwun@swri.org](mailto:hkwun@swri.org)