

National Pipeline Mapping System An Operator's Perspective


**Presentation at the PHMSA Public Workshop
National Pipeline Mapping System
Arlington, VA
November 17, 2014**

Jerome Themig



DISCLAIMER

- The pipeline operations of local distribution operators are very diverse.
- The actions proposed to address the changes to the National Pipeline Mapping System depend on the specific characteristics of the pipeline system and current GIS data.
- The actions proposed will vary with different operators.




Agenda

- Ameren Illinois Background
- What Information is currently in Ameren Illinois' Mapping System
- What Active Steps are Underway to Update Information
- Timeframe and Resources Required
- Challenges in Meeting PHMSA's Request
- Summary

AMEREN ILLINOIS BACKGROUND

- Regulated electric and gas delivery company based in Collinsville, Illinois
- Parent company is Ameren Corporation located in St Louis, Missouri
- Service territory spans 43,700 square miles, or about three quarters of the State of Illinois
- Deliver safe, reliable energy to more than 1,200 communities serving 1.2 million electric and 806,000 natural gas customers in central and southern Illinois
- Gas delivery system includes approximately 1,250 miles of transmission pipelines, 16,950 miles of distribution mains and 12 underground natural gas storage fields
- Peak day delivery of 1,385,000 MCF and with an annual throughput of 155 BCF

AMEREN ILLINOIS PIPELINE SYSTEM



AMEREN ILLINOIS TRANSMISSION PIPELINE SYSTEM

- 1,250 miles of coated/cathodically protected steel pipe
- Sizes 2" through 30"
- Installed in 1930's through 2013
- 77% in Class 1 and Class 2 Locations
- 23% in Class 3 Locations




AMEREN ILLINOIS MAPPING SYSTEM(S)

- Attribute information currently available in GIS for future NPMS submission
 - Pipe Diameter
 - MAOP
 - Installation Date
 - Wall Thickness
 - Pipe Grade

Field Name	Field Type ¹	Field Length	Short Description	Full Description	Acceptable Values (UPPERCASE)	Required Field ²
OPER_LINK	I	8	Unique Link ID	Link between the geospatial elements (pipeline segments) and their respective attribute records. Assigned by the operator or the operator's software package (i.e., COVER-ID, MSLINK_ID, etc). Note the OPER_LINK and the PLINE_ID may be identical. Note that once processing is complete, the OPER_LINK value will be removed from the data by NPMS staff as it will no longer be needed.	Positive integer	Y-if your attributes are not included in your geospatial file; refer to section 3.4 N - if your attributes are included in your geospatial file..
OPID	I	5	Operator Number	Unique tracking number assigned by PHMSA to the company that physically operates the pipeline system. If you do not know your firm's OPID, check with your DOT/Regulatory Compliance department or the NPMS Web site.	Positive integer	Y
OPER_NM	C	40	Operator Name	The company name that physically operates the pipeline system.	Character	Y
SYS_NM	C	40	System Name	Assigned by the operator. The operator's name for a functional grouping of pipelines.	Character	Y
SUBSYS_NM	C	40	Sub System Name	Assigned by the operator. A unique name for a smaller sub-section of a pipeline system. A subset of SYS_NM.	Character	N
PLINE_ID	C	20	Pipeline ID	Assigned by the operator. This is a unique identifier for a specific section of pipeline within a pipeline system.	Character	Y
DIAMETER	D	5	Diameter	Nominal diameter of the pipeline segment, in inches (two decimal places, ##.##).	Real Number	N
COMMODITY	C	3	Commodity Category	Abbreviation for the primary commodity carried by the pipeline system. CRD=crude oil, PRD=non-HVL product, AA=anhydrous	CRD, PRD, AA, LPG, NGL, OHV, CO2, ETH, EPL,	Y

AMEREN ILLINOIS MAPPING SYSTEM(S)

- Attributes in GIS mapping system
 - Class Location
 - HCA



AMEREN ILLINOIS MAPPING SYSTEM

- Level of Accuracy
 - Between 50' to 200'
 - Completed 200 miles of GPS surveys
 - Five year plan to survey remaining transmission pipelines



STEPS UNDERWAY TO UPDATE INFORMATION

- MAOP Record Review and Analysis
- Center Line Surveys
- Conflation

Location of Ameren mains on Bing map



Moving facilities in a GIS to a spatially accurate location

After Conflation



STEPS PROPOSED TO UPDATE GIS INFORMATION

- Additional GIS attributes:
 - Internally Inspectable
 - SMYS
 - HCA
 - PIR
 - Mill Test
 - Risk Area
 - System MAOP Method
 - Attachment of Legacy Record

Attribute Name	Attribute Value
STOCK NUMBER*	02007
WALL THICK*	17.3%
WALL SPEC*	0.212
WELD SPEC*	12000
SEAM SPEC*	UNKNOWN
COATING TYPE*	UNKNOWN
SCR*	N/A
POLY TYPE*	N/A
JOINT TYPE*	UNKNOWN
COATING?	YES
TRACER CABLE?	UNKNOWN
CASING?	NO
INSERT SIZE	N/A
INSERT MATERIAL	N/A
INSERTION COMMENT	
INSTALL TYPE*	DIRECT BURY
CLASS LOCATION*	1
CROSS TYPE*	N/A
WORK TYPE*	UNKNOWN
PATROL DESIGNATION	N/A
LINE DESIGNATION	TRANSMISSION
CONTRACT NUMBER	
PROJECT CROSS REFERENCE	
DEPTH	0
LOCATION (FROM)	
LOCATION (TO)	
FIG_ORIG	1854965
PIR COMPONENT	
LENGTH (ACTUAL)	248.8
LENGTH (GRAPHIC)	248.8
LAST SAVED (U)	

CHALLENGES IN MEETING PHMSA'S REQUEST

- Approximately 10,000 transmission main segments
 - Twenty plus data points for each segment
 - Verification of over 200,000 data attributes
- Spatial accuracy of current mapping system
 - Relative to Ameren Illinois Land Base
 - Not Google Earth
- Most historical records are paper format
- Electronic records may not be in PHMSA's desired format
- New attributes may not be maintained in GIS system
- Significant time and resources required to complete this request

SUMMARY

- **GIS Origin**
 - Conversion of paper maps with data base component
 - Data inputs from paper sources (i.e. maps & records)
- **Current GIS Land Base**
 - Provides location of facilities in reference to commercial land base
 - Not true with Google Earth
- **Multi-Year Efforts Planned or Underway**
 - Centerline Surveys
 - Conflation
 - Document Management
- **Five Plus Years for Transmission Pipelines**
- **Limited Resources – Competing Projects**
 - MAOP Verification, Review, and Data Integration
 - Integrity Verification Process
 - Replacement of Aging Infrastructure
- **Security of Data**