

PUBLIC PAGE

COMPREHENSIVE STUDY TO UNDERSTAND LONGITUDINAL ERW SEAM FAILURES

Submitted by, Battelle in collaboration with
Kiefner and Associates Inc (KAI), and Det Norske Veritas (U.S.A.), Inc. (DNV)

Contact: Battelle Memorial Institute
505 King Avenue, Columbus, OH 43201,
Battelle PI: Brian Leis (614) 424-4421; (614) 458-4421 (fax); leis@battelle.org

Contract Number: DTPH56-11-T-000003
For quarterly period ending: Nov 26, 2011

The objective of the proposed project is to assist the PHMSA in favorably closing NTSB Recommendation P-09-1 arising from the Carmichael MS pipeline rupture involving an ERW seam, which directed that the PHMSA conduct a comprehensive study of ERW pipe properties and the means to assure that they do not fail in service. The work is anticipated to validate that periodic use of the current ERW seam integrity assessment methods (hydrostatic testing and in-line inspection using a crack-detection tool) are the best means to prevent ERW seam ruptures. The work will address the characteristics of ERW seams that make them susceptible to failure, and it will identify the factors the pipeline operators must consider in order to assure that their ERW pipelines are safe. .

In this quarter, the data collected on operator's experience with early generation ERW pipelines, focusing on the effectiveness of in-line inspection and hydrotesting as they apply to verifying the integrity of early generation ERW pipelines is being assessed to show the track record of hydrostatic testing, the track record of in-line inspection, and review of U.S. vintage seam failures. We will continue to collect problem pedigree pipe removed and have it shipped to Battelle for cleaning and assessment. The challenge remains to acquire pipe samples in a timely fashion and get the program back on schedule. We also continued collection, organization, and review of relevant literature on selective seam weld corrosion, develop outline of literature review report, finish screening and characterization evaluation of ERW pipe samples, and begin evaluation of in-ditch susceptibility measurement concepts, construct test setup for mitigation tests and initiate mitigation.